

C² REMOVE

Easy-to-use C² Remove preps concrete floors for hardening and densifying or other penetrating protective treatments, as well as grinding and polishing. The low-odor cleaner quickly removes a variety of waxes and acrylics – including most lower-solids cure and seals – from concrete floors. That leaves the concrete free of old coatings that can block treatments from penetrating, or clog up the heads on grinding and polishing equipment. Water-rinsable C² Remove can be used in concentrate, or diluted with fresh water, depending on the job.

ADVANTAGES

- Removes waxes, acrylics and most low-solids cure & seals from concrete floors.
- Low odor for interior use.
- Does not affect concrete color.
- Contains readily biodegradable materials.

Limitations

- Surfaces are slippery during application. Use appropriate caution.
- Product efficiency is reduced in cold temperatures.
- May damage synthetic or reflective glass.

TYPICAL TECHNICAL DATA

FORM	Colorless liquid
SPECIFIC GRAVITY	1.05
pH	not applicable
WT/GAL	8.76 lbs
ACTIVE CONTENT	not applicable
TOTAL SOLIDS	not applicable
VOC CONTENT	4% maximum
FLASH POINT	>93°C (200°F) ASTM D3278
FREEZE POINT	not applicable
SHELF LIFE	2 years in tightly sealed, unopened container

REGULATORY COMPLIANCE

VOC Compliance


C² Remove is compliant with all US VOC regulations.

Contact us at sales@cretecolors.com for compliance questions with individual country regulations.

SAFETY INFORMATION

Always read full label and SDS for precautionary instructions before use. Use appropriate safety equipment and job site controls during application and handling.

24-Hour Emergency Information:
INFOTRAC at +1-352-323-3500



PREPARATION

Protect people, vehicles, property, painted surfaces, plants and all surfaces not set for cleaning from product, splash and wind drift. Protect and/or divert pedestrian and auto traffic.

Some metal finishes and glass installed in recent years may be damaged by product. Test or protect if needed.

Surface & Air Temperatures

Cleaning effectiveness is reduced when surface and air temperatures fall below 10°C (50°F).

Do not apply at temperatures below 4°C (40°F). If freezing conditions exist prior to application, let concrete thaw.

Equipment

Apply with a long-handled brush or mop and pump-up sprayer. Use a brush or scrubbing machine for light scrubbing. Use a mop or wet vacuum as needed to take up the spent cleaner and debonded coating.

Pressure-wash (under 1,000 psi; 7 MPa) or mop with fresh water only if needed to remove excess residue.

Storage & Handling

Store in a cool, dry place. Always seal container after dispensing. Do not alter or mix with other chemicals. Published shelf life assumes upright storage of factory-sealed containers in a dry place. Maintain temperatures of 7–38°C (45–100°). Do not double stack pallets. Dispose of unused product and container in accordance with local regulations.

Packaging

3.5L, or 20L containers

APPLICATION

Read “Preparation” and the Safety Data Sheet before use.

ALWAYS TEST a small area of each surface to confirm suitability, coverage rate and desired results before beginning overall application. Test with the same equipment, recommended surface preparation and application procedures planned for general application. Let surface dry thoroughly before inspection.

Dilution & Mixing

Dilute with clean water.

Light Wax Build-up:

1 part product to 10 parts water

Heavy Wax Build-up:

1 part product to 3 parts water

Low-Solids Cure & Seals:

Full strength

Coverage Rates

Coverage varies based on concrete porosity and texture. Always test.

- 7.5 – 12.5 m²/ liter
- 300 – 500 ft²/ US gallon

Application Instructions

1. Apply with low-pressure spray.
2. Allow to dwell for 5–10 minutes.
3. Scrub with a stiff bristle brush or a mechanical scrub machine.
4. Take up as much spent cleaner and dissolved coating as possible.
5. Rinse or mop the floor with fresh water, if needed.

Cleanup

Clean tools and equipment with fresh water.

BEST PRACTICES

Allow more dwell time for C² Remove in temperatures below 10°C (50°F). In rare instances where floors are exposed to freezing temperatures, make sure the concrete is thawed out and surface temperature is above 4°C (40°F).

All loose construction debris and foreign materials from surfaces to be treated must be removed using a dry broom. For oily spot cleaning, use C² Stain Clean.

Make sure cleaned floors are free as possible of spent cleaner and debonded coatings. A thorough mop, wet-vac or machine scrub usually gets up enough residue so the cleaned floor can be treated, once dry.

Surfaces are slippery during application. Use appropriate caution. If needed, mop or pressure-rinse the cleaned floor with fresh water to flush away excess.



WARRANTY

The information and recommendations made are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application of our products, nor anticipate every variation encountered in masonry surfaces, job conditions and methods used. The purchasers shall make their own tests to determine the suitability of such products for a particular purpose.

Crete Colors International warrants this product to be free from defects. *Where permitted by law, Crete Colors makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose.* The purchaser shall be responsible to make his own tests to determine the suitability of this product for his particular purpose. Crete Colors International's liability shall be limited in all events to supplying sufficient product to re-treat

the specific areas to which defective product has been applied. Acceptance and use of this product absolves Crete Colors from any other liability, from whatever source, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability.

This warranty may not be modified or extended by representatives of Crete Colors, its distributors or dealers.

CUSTOMER CARE

Factory personnel are available for product, environment and job-safety assistance with no obligation. Email us at sales@cretecolors.com for technical support.

Factory-trained representatives are established in countries around the world. Contact us or visit our web site at www.cretecolors.com, for the name of the Crete Colors representative in your area.