

GA9080FX1 Makita

230mm (9") 2,400W Angle Grinder

240v



230mm (9") 2,400W Angle Grinder

Harness the might of the 2,400W motor in the 230mm (9") angle grinder (GA9080FX1) and witness unparalleled performance to tackle the toughest applications. In addition to heavy duty power, the GA9080FX1 comes standard with features like anti-restart protection to better protect the user. If power is disrupted while using the grinder and the switch remains in the on position, the GA9080FX1 will not restart until the user releases and reengages the two-stage trigger switch. The built-in soft start module will reduce initial start-up shock, allowing the user to better control the unit while it rapidly achieves full power.

The GA9080FX1 includes numerous ergonomic features that allow the user to work comfortably for extended periods, while achieving consistent results. The main handle is equipped with anti-vibration technology to significantly reduce vibration passing from the workpiece to the user's hands. The handle can also be rotated 90° left or right allowing the users to optimally control the grinder across various applications. Finally, the vibration proof side grip is rubberised and has been positioned to enhance tool maneuverability and balance.



Product Overview

240V

Soft Start

Torque Limiter

Anti-Restart Protection

Super Flange Compatible

Anti-Vibration Housing

Two-Stage Trigger Switch

Rotatable Rear Handle

High Performance 2,400W Motor

Vibration Proof Side Grip



Product Specification Sheet

240V



Wheel Diameter	230mm (9")
Hole Diameter	22.23mm
Spindle Thread	M14
No Load Speed	6,600rpm
Continuous Rating Input	2,400W
Overall Length	509mm
Net Weight	6.5kg
Power Supply Cord	2.0m

- **Soft Start** – When the switch is pressed the wheel will start slowly to reduce initial start up shock, then rapidly accelerate to maximum speed.
- **Torque Limiter** – The power is limited at start-up and during heavy duty applications in order to protect the tools mechanical components.
- **Anti-Restart Protection** – If there is a power disruption and the switch remains in the on position the tool will not restart until the user releases and reengages the two-stage trigger switch.
- **Super Flange Compatible** – The super flange is a thicker inner flange that can be used on larger angle grinders (7+9") without mechanical brakes fitted, this means less effort is required to undo the lock nut compared to the conventional inner flange.
- **Anti-Vibration Housing** – The GA9080X1 also features an anti-vibration housing to help minimise user fatigue.
- **Two-Stage Trigger Switch** – The switch requires two stages of action before the tool will start, this helps avoid accidental operation. The tool will shut down if the user releases the trigger switch and will need to be reengaged.
- **Rotatable Rear Handle** – The rear handle can be rotated and locked into different positions allowing the user to better control the tool across multiple applications.
- **High Performance 2,400W Motor** – Features a powerful 2,400-watt motor for industrial applications.
- **Vibration Proof Side Grip** – The inclusion of a vibration proof side grip allows users to better control the tool ergonomically.

Performance



2,400-Watt motor allows for continuous heavy-duty operation.

Protection



Anti-restart protection and soft start to enhance user safety.

Durability



Engineered for increased durability and longer tool life.

Comfort



Anti-vibration housing and vibration proof side grip minimise user fatigue.


Makita Super Flange

The GA7080FX1 and GA9080FX1 come standard with the Makita Super Flange. The super flange is a larger and thicker inner flange that is used on 7+9" (180+230mm) angle grinders without electric or mechanical brakes.

The super flange has a built-in mechanism that allows the user to remove the lock nut with less effort compared to regular inner flanges.




Super Flange



Regular Flange

Standard Accessories		
	194543-3	Vibration Proof Grip
	782034-2	Lock Nut Wrench 35
	224256-3	Outer Flange 78
	224257-1	Inner Flange 78



Optional Accessories

Optional Accessories		
	122913-6	230mm Cutting Guard
	198379-2	230mm Dust Collecting Wheel Guard Plunge
	195354-9	Ezynut Tool-Less Lock Nut
	194305-9	Lock Nut Release Socket 1/2" Square Drive

Optional Accessories		
	Link to Website	Grinding Wheels
	Link to Website	Cutting Wheels
	Link to Website	Diamond Cutting Wheels